

Product Data Sheet

BRAKE FLUID

EXOL BRAKE FLUID DOT 4



Packing Size

500ml **1L** **20L** **25L** **208L**

Product Description

Exol Heavy Duty Brake & Clutch Fluid DOT 4 is a premium glycol type quality automotive Brake fluid meeting the specifications of DOT 4 & DOT 3, SAE J 1704, ISO 4925 and FMVSS No. 116.

Main Benefits

- Low volatility and low pour point ensure performance in normal temperature range.
- Provide protection against rust and corrosion.
- Compatible with rubber seals.
- Good braking response.
- Reduces chances of vapor lock.

Typical Test Data

Test	Test Method	Units	Typical Reports
Appearance	Visual	None	Clear & Bright
Density @ 20° C	IP 160	g/ml	1.05
Viscosity, cSt @ 40° C	IP 71	°C	Max. 1500
Viscosity, cSt @ 100° C	ASTM D445	mm ² /s	Min. 2.10
Water	ASTM D1123	% wt	0.2
ERBP ° C (dry)	ASTM D1120	°C	260
ERBrC (Wet)	SAE J1703	°C	160
pH Value	SAE J1703	pH	7.5

Health & Safety

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Storage

All packaged products should be stored under covered Storage. If Covered Storage is not possible for Drum packaging, Storage can be done outside storage and drums should be laid horizontally to prevent water seepage. Products should not be stored above 60°C or freezing conditions.

January 5, 2014

The Contents of this Product Data Sheet are believed to be accurate as of date of printing. However, we do not provide any warrant or representation, express or implied, with respect to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and should be utilized as a guide only. Please refer to latest version of this Data Sheet or request the same as necessary. Users must assess the suitability of application and comply with all local laws and regulations. Users must evaluate the product and use them safely. Please refer to our Material Safety Data Sheet to understand information regarding, storage, handling, and disposal of the product. Gulf Worldwide Distribution FZE or its subsidiaries does not take any responsibility for any damage or injury caused due to improper or abnormal use of product, inherent hazards in nature of product or failure to follow recommendations of Material Safety Data Sheet. Please contact us for any further information or guidance.

