

EXTREME PERFORMANCE ENGINE OILS & LUBRICANTS



Product Data Sheet

GREASE

EXOL GREASE MULTI PURPOSE LITHIUM GENERAL PURPOSE

Product Description

EXOL GREASE DGMT 3 is a Superior Quality, Multipurpose Grease. It can be used for a wide range of Industrial & Automotive Applications. It is a Lithium Soap Complex Lubrication Grease for all types of Rolling Bearings & Relative Moving parts.

Main Benefits

- Exceptionally long grease life.
- Outstanding Oxidation Stability.
- High Mechanical Stability.
- Excellent Water Resistance.
- Good Anti-wear Properties.
- Good Rust Prevention Properties.

Typical Test Data

| Test Parameters | Test Method | Gen. Purpose |
|---|----------------------|---------------------------|
| Thickener Type | | Lithium |
| NLGI Classifications | | NLGI-3 |
| Texture | | Smooth |
| Colour | Visual | Pale Light Yellow |
| Drop Point °C | ASTM D 566 | 200 |
| Temperature Range | | -30 to 120 C -22 TO 250 F |
| Base Oil Viscosity @ 100 °C | ASTM D-445 | 11.1 |
| Flash Point of Base Oil °C | ASTM D-92 | 240 |
| Worked Penetration @ 25 °C 6D X | ASTM D-217 | 245 |
| Working Stability 6D/100000 X | ASTM D-217 / 4290 | - |
| Copper Corrosion 24hrs 100 °C | ASTM D-4048 / CMM161 | Negative |
| Free Acidity (Oleic) by mass | ASTM D-128 / IP-37 | NIL |
| Free Alkali as Ca (OH2) % by mass | ASTM D -2 / IP-37 | 0.04 |
| Leakage and Deposit Forming Tendencies (Wheel Bearing Test) Leakage in gms. Depositions on racer roller Evidence of abnormal changes in consistency / Structure | ASTM D-1263 / 4290 | Pass |

Packing Size

11.

4L

5L

20L 2

20

Health & Safety:

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

October 1, 2014

The Contents of this Product Data Sheet are believed to be accurate as of date of printing. However, we do not provide any warrant or representation, express or implied, with respect to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and should be utilized as a guide only. Please refer to latest version of this Data Sheet or request the same as necessary. Users must assess the suitability of application and comply with all local laws and regulations. Users must evaluate the product and use them safely. Please refer to our Material Safety Data Sheet to understand information regarding, storage, handling, and disposal of the product. Gulf Worldwide Distribution FZE or its subsidiaries does not take any responsibility for any damage or injury caused due to improper or abnormal use of product, inherent hazards in nature of product or failure to follow recommendations of Material Safety Data Sheet. Please contact us for any further information or guidance.

Gulf Worldwide Distribution FZE MO 0253 Jebel Ali Freezone PO Box 261619, Dubai U.A.E.

Tel: +9714 8814100 | **Fax:** +9714 8814343

E-mail: sales@exol.ae **Web:** www.exol.ae





