

Product Data Sheet

MOTORCYCLE OIL

EXOL SPEED 4T
SAE 20W - 50
API SJ

Packing Size

1L **750ml**



Product Description

EXOL SPEED is future oriented engine oil which has especially produced for 4 stroke motorbikes. It provides fuel saving operation of engines. It fulfills the high tech demands of the latest powerful engine generations. It also meets the high performance low friction engine oil for all motorbikes. It is a superior quality lubricant formulated with highly refined base stock and advanced additive technology.

Main Benefits

- Quick Lubrication
- Longer drain interval.
- Engine cleanliness and low combustion residue.
- Fuel economy and better cold starting.
- Oxidation resistant, good high temperature stability.
- Neutral against sealing material
- Low oil consumption.

Application

Exol 4T 20W-50 Engine Oil is suitable for all modern 4 Stroke engine motorcycles where the manufacturer recommended API specification is SJ or JASO MA2 or earlier.

Typical Test Data

| Description | Test Method | Units | 20W-50 |
|--|-------------|--------------------|----------------------|
| Density @ 15.6 °C Relative | ASTM D4052 | g/ml | 0.875 - 0.885 |
| Viscosity Kinematic @ 100 °C, mm ² /s | ASTM D445 | mm ² /s | 18.0 - 20.0 |
| Viscosity @ 40 | ASTM D445 | mm ² /s | 170-175 |
| Viscosity Index (Calculated) | ASTM D2270 | None | 122 - 130 |
| Viscosity Low Temp. Cranking cP @ Temp °C | ASTM D5293 | mPa.s (cP) | 6500 - 8000 (-15 °C) |
| Flash Point °C (PMCC) | ASTM D93 | °C | >230 |
| Pour Point | ASTM D97 | °C | <-27 |
| Total Base Number, mg KOH/g | ASTM D2896 | Koh/g | 7.0 - 8.0 |
| Sulfated Ash | ASTM D874 | % wt | 1-1.2 |

Health & Safety

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Storage

All packaged products should be stored under covered Storage. If Covered Storage is not possible for Drum packaging, Storage can be done outside storage and drums should be laid horizontally to prevent water seepage. Products should not be stored above 60°C or freezing conditions.

January 5, 2014

The Contents of this Product Data Sheet are believed to be accurate as of date of printing. However, we do not provide any warrant or representation, express or implied, with respect to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and should be utilized as a guide only. Please refer to latest version of this Data Sheet or request the same as necessary. Users must assess the suitability of application and comply with all local laws and regulations. Users must evaluate the product and use them safely. Please refer to our Material Safety Data Sheet to understand information regarding, storage, handling, and disposal of the product. Gulf Worldwide Distribution FZE or its subsidiaries does not take any responsibility for any damage or injury caused due to improper or abnormal use of product, inherent hazards in nature of product or failure to follow recommendations of Material Safety Data Sheet. Please contact us for any further information or guidance.

