

Product Data Sheet

SEMI SYNTHETIC MOTOR OIL

EXOL DISCOVERY

SAE 10W - 40

API SG/CD

Packing Size

1L 4L 5L 20L 25L 208L



Product Description

EXOL DISCOVERY are multigrade engine oils that are designed for all gasoline and diesel powered passenger cars, light trucks and van including those fitted with turbo chargers. It is a superior quality multi grade lubricant formulated with highly refined base stock and advanced additive technology to maintain engine oil cleanliness, wear and very good low temperature fluidity ensure easy starting in cold weather and low volatility contributes to low oil consumption.

Main Benefits

- Fuel economy and better cold starting.
- Excellent engine protection in severe weather conditions.
- Thermal stable. Anti wear, anti oxidant and long drain interval.
- Low oil consumption and turbo proven stability.
- Oxidation resistant, good high temperature stability.

Application

Exol Discovery 10W-40 Semi-Synthetic Engine Oil is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommended API specification is SG/CD or earlier.

Typical Test Data

Description	Test Method	Units	10W-40
Density @ 15.6 °C Relative	ASTM D4052	g/ml	0.870 - 0.880
Viscosity Kinematic @ 100 °C, mm ² /s	ASTM D445	mm ² /s	14.0 - 15.0
Viscosity @ 40	ASTM D445	mm ² /s	95-105.
Viscosity Index (Calculated)	ASTM D2270	None	145 - 155
Viscosity Low Temp. Cranking cP @ Temp °C	ASTM D5293	mPa.s (cP)	5000 - 6500 (-25 °C)
Flash Point °C (PMCC)	ASTM D93	°C	>220
Pour Point	ASTM D97	°C	<-33
Total Base Number, mg KOH/g	ASTM D2896	Koh/g	8.0 - 9.0
Sulfated Ash	ASTM D874	% wt	1-1.2

Health & Safety

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Storage

All packaged products should be stored under covered Storage. If Covered Storage is not possible for Drum packaging, Storage can be done outside storage and drums should be laid horizontally to prevent water seepage. Products should not be stored above 60°C or freezing conditions.

January 5, 2014

The Contents of this Product Data Sheet are believed to be accurate as of date of printing. However, we do not provide any warrant or representation, express or implied, with respect to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and should be utilized as a guide only. Please refer to latest version of this Data Sheet or request the same as necessary. Users must assess the suitability of application and comply with all local laws and regulations. Users must evaluate the product and use them safely. Please refer to our Material Safety Data Sheet to understand information regarding, storage, handling, and disposal of the product. Gulf Worldwide Distribution FZE or its subsidiaries does not take any responsibility for any damage or injury caused due to improper or abnormal use of product, inherent hazards in nature of product or failure to follow recommendations of Material Safety Data Sheet. Please contact us for any further information or guidance.

